












## Modem Pricelist

ITEM	PHOTO	SPECIFICATION	PRICE (USD)	PACKING
ADSL MODEM		<ul style="list-style-type: none"> <li>Full Rate ADSL Router,support Bridge and Route mode</li> <li>Support Various Mainstream DSLAM, up to 8Mbps Downstream and 1Mbps Upstream Date rate</li> <li>The max distance is up to 5.4kilometer</li> <li>Online software upgradeable</li> <li>Support RFC 148BRIDGE,RFC1483 ROUTER</li> <li>Support Classical IP over ATM(RFC1577)</li> <li>Support PPP over ATM(RFC2364)</li> </ul>	18.00	20pcs/CTN 17.8KGS 58.5X29.5X31CM
ADSL MODEM	 温	<ul style="list-style-type: none"> <li>Full Rate ADSL Router,support Bridge and Route mode</li> <li>Support Various Mainstream DSLAM, up to 8Mbps Downstream and 1Mbps Upstream Date rate</li> <li>The max distance is up to 5.4kilometer</li> <li>Online software upgradeable</li> <li>Support RFC 148BRIDGE,RFC1483 ROUTER</li> <li>Support Classical IP over ATM(RFC1577)</li> <li>Support PPP over ATM(RFC2364)</li> </ul>	20 . 00	20pcs/CTN 17.8KGS 58.5X29.5X31CM
ADMTEK9 83B		<ul style="list-style-type: none"> <li>Admtek983b single chip Compliant to PC99/PC2001 standard</li> <li>Single UTP/STP port for both 10Base-T and 100Base-TX</li> <li>Support Wake-on-LAN function and remote wake-up(OPTION)</li> <li>LED indicator for installation verification and diagnostic purpose</li> </ul>	2.00	100pcs/CTN 7.5KGS 58.5X29.5X31CM
RTL8139D		<ul style="list-style-type: none"> <li>Rtl8139D single chip Compliant to PC99/PC2001 standard</li> <li>Single UTP/STP port for both 10Base-T and 100Base-TX</li> <li>Support Wake-on-LAN function and remote wake-up(OPTION)</li> <li>LED indicator for installation verification and diagnostic purpose</li> </ul>	2.40	100pcs/CTN 7.5KGS 58.5X29.5X31CM
Modem Smartlink28 00		<ul style="list-style-type: none"> <li>Smartlink2800 double chipsets</li> <li>Support ITU-V.90,ITU-V.92</li> <li>Support Plug and Play</li> <li>Support Data/Fax/Voice</li> <li>Support Win98/Me/2000/XP,etc</li> </ul>	3.00	100pcs/CTN 9.5KGS 58.5X29.5X31CM

<p><b>Modem</b> Intel82536</p>		<ul style="list-style-type: none"> <li>■ Intel82536EP Chipset (same as Ambient 5628C)</li> <li>■ Support ITU-V.90,ITU-V.92</li> <li>■ Support Plug and Play</li> <li>■ Support Data/Fax/Voice</li> <li>■ Support Win98/Me/2000/XP,etc</li> </ul>	<p><b>5.50</b></p>	<p>100pcs/CTN 9.8KGS 58.5X29.5X31CM</p>
<p><b>Modem</b> CONEXANT1252</p>		<ul style="list-style-type: none"> <li>■ CONEXANT11252 chipset</li> <li>■ Support ITU-V.90,ITU-V.92</li> <li>■ Support Plug and Play</li> <li>■ Support Data/Fax/Voice</li> <li>■ Support Win98/Me/2000/XP,etc</li> </ul>	<p><b>4.40</b></p>	<p>100pcs/CTN 9.5KGS 58.5X29.5X31CM</p>
<p><b>Modem</b> MOTOROLA MODEM</p>		<ul style="list-style-type: none"> <li>■ Motorola chipsets</li> <li>■ Support ITU-V.90,ITU-V.92</li> <li>■ Support Plug and Play</li> <li>■ Support Data/Fax/Voice</li> <li>■ Support Win98/Me/2000/XP,etc</li> </ul>	<p><b>3.10</b></p>	<p>100pcs/CTN 9.5KGS 58.5X29.5X31CM</p>
<p><b>8 PORT SWITCH</b></p>		<ul style="list-style-type: none"> <li>■ Complies with IEEE 802.3/802.3u Ethernet standards</li> <li>■ 810/100Mbps UTP/STP ports</li> <li>■ Full and half duplex support</li> <li>■ Provides non-blocking and non-head-of-line-blocking forwarding</li> <li>■ Automatic source address learning</li> <li>■ Broadcast storm filtering control</li> <li>■ Supports TP interface Auto MDIX function for auto TX/RX swap</li> </ul>	<p><b>6.80</b></p>	<p>40pcs/CTN 24.3KGS 66X52.3X29.5CM</p>
<p><b>5 PORT SWITCH</b></p>		<ul style="list-style-type: none"> <li>■ 10/100 Base-T standard Ethernet Switch</li> <li>■ 5 UTP RJ45 port ,1 UPLINK port</li> <li>■ IEEE 802.3,IEEE802.3u,IEEE 802.3X</li> <li>■ Full-duplex and half-duplex on all ports</li> <li>■ CSMA/CD protocol for complete data integrity</li> <li>■ Expandable with hub-to-hub cascading</li> </ul>	<p><b>5.50</b></p>	<p>40pcs/CTN 22.0KGS 66X52.3X29.5CM</p>
<p><b>16 PORT SWITCH</b></p>		<ul style="list-style-type: none"> <li>■ Complies with IEEE 802.3/802.3u standards</li> <li>■ Full and half duplex support</li> <li>■ IEEE802.3x flow control support</li> <li>■ Support TP interface Auto MDIX function</li> <li>■ Support smart config port(option)</li> <li>■ Desktop size for SOHO using</li> <li>■ VLAN and TRUNK functions are option</li> </ul>	<p><b>22.00</b></p>	<p>10pcs/CTN 13.2KGS 53.5X46X29CM</p>

<p><b>16 PORT SWITCH</b></p>		<ul style="list-style-type: none"> <li>■ Standard 19" rack mount</li> <li>■ Complies with IEEE 802.3/802.3u standards</li> <li>■ Full and half duplex support</li> <li>■ IEEE802.3x flow control support</li> <li>■ Support TP interface Auto MDIX function</li> <li>■ Supports VLAN&amp;Home VLAN function</li> <li>■ Grouping 4 physical links in maximum to a large logical trunk(800Mbit/s)</li> <li>■ Supports QoS function on each port</li> </ul>	<p><b>23.00</b></p>	<p>5pcs/CTN 13.2KGS 53.5X46X29CM</p>
<p><b>24 PORT SWITCH</b></p>		<ul style="list-style-type: none"> <li>■ Standard 19" rack mount</li> <li>■ Complies with IEEE 802.3/802.3u standards</li> <li>■ Full and half duplex support</li> <li>■ IEEE802.3x flow control support</li> <li>■ Support TP interface Auto MDIX function</li> <li>■ Supports VLAN&amp;Home VLAN function</li> <li>■ Grouping 4 physical links in maximum to a large logical trunk(800Mbit/s)</li> <li>■ Supports QoS function on each port</li> </ul>	<p><b>28.00</b></p>	<p>5pcs/CTN 14.5KGS 53.5X46X29CM</p>
<p><b>4 PORT USB HUB</b></p>		<ul style="list-style-type: none"> <li>■ Compliant to USB specification Revision 2.0</li> <li>■ 4 downstream ports</li> <li>■ Upstream port supports both high-speed (HS) and full-speed (FS) traffic</li> <li>■ Downstream ports support HS, FS, and low-speed (LS) traffic</li> <li>■ 1 control pipe (endpoint 0, 64-byte data payload) and 1 interrupt pipe (endpoint 1, 1-byte data payload)</li> <li>■ Backward compatible to USB specification Revision 1.1</li> </ul>	<p><b>2.40</b></p>	
<p><b>PCI-USB 4PORT1.1/2.0</b></p>	 <p>深圳市鑫富三电子有限公司 alibaba.com.cn</p>	<ul style="list-style-type: none"> <li>■ Compliant with Universal Serial Bus Specification Revision 2.0</li> <li>■ Compliant with Enhanced Host Controller Interface Specification Revision 1.0</li> <li>■ Compliant with Universal Host Controller Interface Specification Revision 1.1</li> <li>■ PCI multi-function device consists of two UHCI Host Controllers for full/low-speed signalling and one EHCI Host Controller core for high-speed signalling</li> <li>■ 4 downstream facing ports in the root hub with integrated physical layer transceivers shared by UHCI and EHCI Host Controllers</li> <li>■ Supports PCI-Bus Power Management Interface Specification release 1.1</li> <li>■ Legacy support for all downstream facing ports</li> <li>■ 4 DMA engines with pipelined control for USB data transfer bandwidth improvement</li> <li>■ Dynamic clock stop control for power consumption reduction</li> </ul>	<p><b>3.20</b></p>	<p>100pcs/CTN 11KGS 67.5X32.5X31CM</p>

<p>PCI-USB2 PORT1.1/ 2.0</p>		<ul style="list-style-type: none"> <li>■ Compliant with Universal Serial Bus Specification Revision 2.0</li> <li>■ Compliant with Enhanced Host Controller Interface Specification Revision 1.0</li> <li>■ Compliant with Universal Host Controller Interface Specification Revision 1.1</li> <li>■ PCI multi-function device consists of two UHCI Host Controllers for full/low-speed signalling and one EHCI Host Controller core for high-speed signalling</li> <li>■ 2 downstream facing ports in the root hub with integrated physical layer transceivers shared by UHCI and EHCI Host Controllers</li> <li>■ Supports PCI-Bus Power Management Interface Specification release 1.1</li> <li>■ Legacy support for all downstream facing ports</li> <li>■ 2 DMA engines with pipelined control for USB data transfer bandwidth improvement</li> <li>■ Dynamic clock stop control for power consumption reduction</li> </ul>	<p><b>3.10</b></p>	<p>100pcs/CTN 10KGS 67.5X32.5X31CM</p>
<p>BROADB AND ADSL ROUTE</p>		<ul style="list-style-type: none"> <li>■ 10/100Mbps Half/Full Duplex MII/Reversed MII wire speed NAPT (PAT)for LAN/WAN interface of Multicast Pass Through</li> <li>■ 100Mbps throughput for upstream and downstream traffic regardless of packet size</li> <li>■ Protocols: NAPT(PAT), DHCP server/client, ICMP, ARP, PPPoE, PPP, PAP, CHAP, PPTP, IPSEC pass through</li> <li>■ DHCP server provides 253 internal private IP</li> </ul>	<p><b>10.00</b></p>	
<p>VoIP Adaptor</p>		<ul style="list-style-type: none"> <li>■ Continue to make and receive regular calls as you normally do</li> <li>■ Make and receive Skype™ calls using your standard telephone</li> <li>■ Forward Skype™ calls to your mobile phone</li> <li>■ Make Skype™ calls from your mobile phone even when you are away from your computer</li> <li>■ Switch between a Skype™ call and a regular phone call</li> </ul>	<p><b>23.00</b></p>	